


Model: **IC 800T**
CEILING SPEAKER




EN



Output selector

IC 800T




Power Taps (70V)	1,5W(3k2Ω)/3W(1k6Ω)
Power Taps (100V)	3W(3k3Ω)/6W(1k6Ω)
Low Impedance position	8Ω
Sensitivity (1W/1m)	92 dB
Frequency Response	50Hz - 18kHz
Dimensions	Ø 270 x 170 mm
Mounting Hole	Ø 240 mm
Material (front baffle)	ABS
Material (grille)	Iron
Weight	2,3 Kg

Specifications are subject to change without notice

Modelo: **IC 800T**
ALTAVOCES DE TECHO




ES



Selector de salida

IC 800T



Posic. de potencia (70V)	1,5W(3k2Ω)/3W(1k6Ω)
Posic. de potencia (100V)	3W(3k3Ω)/6W(1k6Ω)
Posic. baja impedancia	8Ω
Sensibilidad (1W/1m)	92 dB
Respuesta en frecuencia	50Hz - 18kHz
Dimensiones	Ø 270 x 170 mm
Agujero de montaje	Ø 240 mm
Material (panel)	ABS
Material (rejilla)	Hierro
Peso	2,3 Kg

Especificaciones sujetas a cambio sin previo aviso